

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

E #19  
6/19/95  
JH

In re Application  
BERNA, Philippe et al  
Serial No. 08/321,589  
Filed: Oct. 12, 1994  
For: PROCESS FOR MAKING A  
VERSATILE CLAMPING DEVICE  
DESIGNED TO HOLD OBJECTS  
WITHOUT DAMAGING THEM, SUCH  
A DEVICE AND ITS USE

FAX COPY RECEIVED

JUN 12 1995

GROUP 3200

Group Art Unit: 3206  
Examiner: Tom Hughes

Molières-sur-Cèze, France  
June 10, 1995

SUPPLEMENTAL AMENDMENT

Hon. Commissioner of Patents and Trademarks  
Washington, D.C. 20231

Sir:

Please before any action, amend the present application as follows:

IN THE CLAIMS

Rewrite claims 1-14 in amended form and insert new claims 15-18:

*E. 1-14*  
1. (four times amended) The method of making a multipurpose device for holding objects by clamping without damaging them comprising the steps of:

a) providing a cylindrical support part [, such as a rod or a tube,] with a section circular or not,

b) placing on said support part [at least] two [movable and removable] arms of which one at least is movable, that is to say can slide along said support part [and be turned around it into at least one direction and which can be easily slipped off said support part and onto it again],

c) securing to [fitting out] at least one of said two [the movable] arms at a single distance from said support part with one substantially elastic buffer having a contact face which is essentially at a right angle to said support part and under which the thickness is large enough so that said buffer could act as a compression spring.

2. (four times amended) A multipurpose device for holding objects by clamping without damaging them, comprising:

- a cylindrical support part [, such as a rod or a tube,] with a section circular or not,

- [at least] two [movable and removable] arms of which one at least is movable, that is to say can slide along said support part [and be turned around it into at least one direction and which can be easily slipped outwards thereof off said support part and onto it again],

- and [at least] one substantially elastic buffer secured to at least one of [the] said two arms at a single distance from said support part, said buffer